

GAS HOSE CONNECTOR & QUICK DISCONNECT DEVICES FOR PORTABLE APPLIANCES (CSA TYPE)

戶外型天然瓦斯器具連接軟管與快拆裝置（CSA）



TYPE G2068 GAS HOSE CONNECTOR

- 鍍鋅鐵皮製成，表面被覆符合 RoHS 之耐候 PVC 材料。
- 具多方向彎曲撓性。
- 耐溫範圍：-40°C~93.5°C
- 工作壓力：1/2 PSI MAX
- 遵照 ANSI Z21.54/CSA 8.4 製作，登錄號碼：1862352
- 包裝長度：依客戶需求製作
- Galvanized steel core, RoHS compliant PVC jacketed
- High flexibility
- Temperature range: -40°C~93.5°C
- Working pressure: 1/2 PSI (3.5KPA)
- Meets ANSI Z21.54/CSA 8.4, file #1862352
- Packing length: By request

Catalog Number	Nominal Size	Inner Diameter		Outside Diameter		Min. Bending Diameter
		Min.	Max.	Min.	Max.	
		mm	mm	mm	mm	
G20680300	3/8"	9.50	10.00	15.50	16.60	89.0
G20680400	1/2"	12.29	12.80	18.50	19.00	102.0

TYPE G0905 QUICK DISCONNECT DEVICE

- 遵照 CSA 6.9+6.9a 以黃銅製成，登錄號碼：1862352。
- 工作壓力：1/2 PSI MAX
- 最大流量：40K BTU
- Brass body
- Meets ANSI Z21.41/CSA 6.9, File #1862352
- Working Pressure: 1/2 PSI (3.5KPA).
- Max. Flow Capacity: 40K BTU

Catalog Number	Max. Working Pressure	Flow Capacity Max.	Inlet Connection	Outlet Connection
G09050300	1/2 PSI (3.5KPA)	36K BTU/HR	NPT-3/8"-18	5/8-18 UNF
G09050400	1/2 PSI (3.5KPA)	76K BTU/HR	NPT-1/2"-14	5/8-18 UNF